

PF	Product Fiche according to (EU) No 65/2014			
S	Supplier's name or trade mark	PYRAMIS		
M	Model identifier	065030401 OVAL CHIMNEY 60		
	Annual Energy Consumption	AEC hood	121.4	kWh/a
	Energy Efficiency Class	EEL class	D	
	Fluid Dynamic Efficiency	FDE hood	15.6	%
	Fluid Dynamic Efficiency class	FDE class	D	
	Light Efficiency	LE hood	14.0	lux/W
	Lighting Efficiency Class	LE class	D	
	Grease Filtering Efficiency	GFE hood	80.7	%
	Grease Filtering Efficiency class	GFE class	C	
	Minimum Air Flow in normal use	Q min	348	m³/h
	Maximum Air Flow in normal use	Q max	595	m³/h
	Air Flow at intensive/boost setting	Q boost	/	m³/h
	A-weighted Sound Power Emission at minimum speed	SPE min	43	dB(A) re 1pW
	A-weighted Sound Power Emission at maximum speed	SPE max	60	dB(A) re 1pW
	A-weighted Sound Power Emission at intensive or boost speed	SPE boost	/	dB(A) re 1pW
	Power consumption off mode	Po	0.00	W
	Power consumption in standby mode	Ps	0.00	W

Additional Information according to (EU) No 66/2014				
	Time increase factor	f	1.4	
	Energy Efficiency Index	EEL hood	86.1	%
	Measured air flow rate at best efficiency point	Q bep	392.0	m³/h
	Measured air pressure at best efficiency point	P bep	318	Pa
	Maximum air flow	Q max	595	m³/h
	Measured electric power input at best efficiency point	W bep	221.7	W
	Nominal power of the lighting system	WL	6.8	W
	Average illumination of the lighting system on the cooking surface	E middle	92	lux